

NORDIC
 HYDRAULIC TRUCK HOISTS
 UNDERBODY SERIES

"TL" Series Features Four-Way Mount

Mount in Conventional or Reverse Direction with the header tee pivot up or inverted for advantages such as weight transfer to front axle, low mounting and ease of installation.



C90



DH90



TL2627



NTL4.5-3

UNDERBODY OPTIONS



BODY PROP



GEAR PUMP, VALVE, RESERVOIR COMBO



12 VOLT DC POWER PACK



H.D. REAR HINGE



STANDARD REAR HINGE



HYDRAULIC CYLINDER

MODEL	C90	DH90	TL1522	TL1627	TL2522	TL2627	NTL4.5-3
No. of Cylinders	1	1	1	1	2	2	2
Cylinder Bore (Inches)	5	5	5	6	5	6	4.5
Piston Stroke (Inches)	14	16	20	27	20	27	91
Piston Rod Dia. (Inches)	2.25	2.25	2.25	2.5	2.25	2.5	TELESCOPIC
Mounting Height (Inches)							
Low-Mount Installation	N/A	6.5	7.75	7.75	7.75	8.75	9.5
Hi-Mount Installation	10.75	6.5	12.75	12.75	12.75	12.75	9.5
Recommended Long Beams (Ins)							
Low-Mount Installation (With Cross Sills)	N/A	6	7	7	7	8	8
Hi-Mount Installation (Without Cross Sills)	10	6	12	12	12	12	10
Weight – Approx. (Pounds)	336	444	598	800	887	1187	928

DEMAND  NORDIC POWER
 FOR RUGGED DEPENDABLE LIFT PERFORMANCE